

VORTEX

POWDER FREE NITRILE EXAMINATION GLOVES



Dental City Vortex Nitrile Powder Free Examination Gloves

SAFETY DATA SHEET (SDS): HEALTH HAZARD DATA

Primary material — Nitrile Rubber. This product is not made with natural rubber latex. Components used in making gloves may cause allergic reactions in some users. If reactions are suspected cease using the product. High quality nitrile gloves provide an excellent biological barrier, they are not recommended for use against chemical exposure. For more information, please call us in the USA at 800-353-9595.

TECHNICAL SPECIFICATIONS, STANDARDS, CERTIFICATIONS:

STORAGE: Avoid direct sunlight. Store in a cool and dry place.

MATERIAL: Nitrile

TYPE: Non Sterile

GLOVE DESIGN & FEATURE: Ambidextrous and finger textured.

CUFF: Beaded

USAGE: For single use only.

COLOR: Blue-3

PACKAGING: 100 ± 4 pcs/inner by weight, 20 inners/carton

POWDER LEVEL: Max. 2 mg/glove

COMPLIANCE STANDARDS: ASTM D6319, EN 455 Part 1, 2, 3 & 4

| | | Inspection Level | AQL |
|------------------------|---------------------|------------------|-----|
| INSPECTION CRITERIA: | Watertight Test | G1 | 1.5 |
| (Sampling & Inspection | Major Defects | G1 | 2.5 |
| ISO 2859) | Minor Defects | G1 | 4.0 |
| | Dimensions | S2 | 4.0 |
| | Physical Properties | S2 | 4.0 |

QUALITY ASSURANCE: ISO 9001 and ISO 13485 certified

ISO 510K, CE Certification

MADE IN CHINA

DIMENSIONS:

| SIZE | PALM WIDTH (mm) | | LENGTH (mm) | | |
|------|-----------------|--------------|--------------|----------|--|
| | ASTM D6319 | VORTEX | ASTM D6319 | VORTEX | |
| XS | 70 ± 10 | 70 ± 10 | 240 ± 10 | 240 ± 10 | |
| S | 80 ± 10 | 80 ± 10 | 240 ± 10 | 240 ± 10 | |
| M | 95 ± 10 | 95 ± 10 | 240 ± 10 | 240 ± 10 | |
| L | 110 ± 10 | 110 ± 10 | 240 ± 10 | 240 ± 10 | |
| XL | 120 ± 10 | 120 ± 10 | 240 ± 10 | 240 ± 10 | |

THICKNESS:

| Location of Thickness | SINGLE WALL (mm) | | |
|-----------------------|------------------|-----------|--|
| Measurement | ASTM D6319 | VORTEX | |
| Finger | Min. 0.05 | .12 ± .05 | |
| Palm | Min. 0.05 | .08 ± .03 | |
| Cuff | N/A | .07 ± .03 | |

PHYSICAL PROPERTIES:

| | BEFORE AGING | | AFTER AGING | |
|------------------------|--------------|----------|-------------|----------|
| | ASTM D6319 | VORTEX | ASTM D6319 | VORTEX |
| Tensile Strength (MPa) | Min. 14 | Min. 14 | Min. 14 | Min. 14 |
| Elongation (%) | Min. 500 | Min. 400 | Min. 400 | Min. 400 |

| ORDERING: | XS | S | M | L | XL |
|-----------|----------|----------|----------|----------|----------|
| ITEM #: | 14-701XS | 14-701SM | 14-701MD | 14-701LG | 14-701XL |

DISTRIBUTED BY: